

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20170605-EX16350  
**Report Reference** EX16350-20150618  
**Issue Date** 2017-JUNE-05

**Issued to:** DUYAR VANA MAKINA SAN VE TIC A S  
Osmangazi Mahallesi 2653  
Sokak No 7  
Esenyurt  
34522 Istanbul TURKEY

**This is to certify that representative samples of** SPRINKLERS, AUTOMATIC AND OPEN  
Refer to addendum page for models.


Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL199, Safety for Automatic Sprinklers for Fire Protection Service

**Additional Information:** See the UL Online Certifications Directory at [www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20170605-EX16350  
**Report Reference** EX16350-20150618  
**Issue Date** 2017-JUNE-05

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Automatic sprinklers incorporating a 5mm glass bulb heat responsive element in the following models, types and temperature ratings.

Listing	SIN	Description	Temperature Ratings, °F
USL	DY3323	Upright 5.6 K, standard response glass bulb style sprinkler plain brass or white painted	135,155,175
USL	DY3327	Pendent 5.6 K, standard response glass bulb style sprinkler plain brass or white painted	135,155,175
USL	DY3423	Upright 5.6 K, quick response glass bulb style sprinkler plain brass or white painted	155
USL	DY3427	Pendent 5.6 K, quick response glass bulb style sprinkler plain brass or white painted	155
USL	DY3329	Horizontal Sidewall 5.6 K, standard response glass bulb style sprinkler plain brass or white painted	135,155,175



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

